



| Nr. / No. | Kabellänge / Cable length (m) | Verpackung / Packing | Innenleiter / Inner conductor        | Ø (mm)   |
|-----------|-------------------------------|----------------------|--------------------------------------|----------|
| 38514     | 0.50                          | bulk                 | 1/0.254 CCS (#30)                    | 6.0±0.2  |
| 45880     | 0.50                          | SB                   |                                      |          |
| 44506     | 1.00                          | bulk                 |                                      |          |
| 45881     | 1.00                          | SB                   |                                      |          |
| 38516     | 1.50                          | bulk                 |                                      |          |
| 45882     | 1.50                          | SB                   |                                      |          |
| 38517     | 2.00                          | bulk                 |                                      |          |
| 45883     | 2.00                          | SB                   |                                      |          |
| 38518     | 3.00                          | bulk                 | 1/0.254 BC (#30)                     | 6.0±0.2  |
| 45884     | 3.00                          | SB                   |                                      |          |
| 44505     | 5.00                          | bulk                 |                                      |          |
| 45885     | 5.00                          | SB                   |                                      |          |
| 38520     | 7.50                          | bulk                 | 1/0.320 BC (#28)                     | 7.0±0.2  |
| 45886     | 7.50                          | SB                   | 1/0.254 CCS (#30)                    |          |
| 38521     | 10.00                         | bulk                 | 7/0.152 BC (#26)                     | 8.0±0.3  |
| 38522     | 15.00                         | bulk                 | 7/0.192 BC (#24)<br>1/0.320 BC (#28) | 10.0±0.4 |
| 38523     | 20.00 w. amplifier            | bulk                 | 7/0.152 BC (#26)<br>1/0.254 BC (#30) | 8.0±0.3  |

### High Speed HDMI™ Kabel mit Ethernet

- HighSpeed HDMI™ für 3D und Ultra HD bis 4K @ 50/60 Hz (2160p)
- HDCP 2.2 konform
- unterstützt Audio Return Channel (ARC) und High Dynamic Range (HDR)
- vergoldete Kontaktflächen für optimale Signalübertragung
- 21:9 - CinemaScope-Seitenverhältnis

Anschlüsse: 2x HDMI™ Standard-Stecker (Typ A)

Datenübertragung: max. 18 Gbit/s

Sonstige Formate: 4K Ultra HD, 4K 3D, HEC, HDR, ARC, Audio 1536 Hz, x.v. Colour (xvYCC), YCbCr 4:4:4, Deep Color (36 Bit), 21:9 Cinemascope

- Isolationswiderstand: 300 V @ 10 MOhm
- Kontaktwiderstand: 5/10 Ohm

- Farbe: schwarz

- Konformität: RoHS konform

### High-speed HDMI™ cable with Ethernet

- High-speed HDMI™ for 3D and Ultra HD up to 4K @ 50/60 Hz (2160p)
- HDCP 2.2 compliant
- supports Audio Return Channel (ARC) and high dynamic range (HDR)
- gold-plated contact surfaces for optimum signal transmission
- 21:9 - CinemaScope aspect ratio

Connectors: 2x HDMI™ Standard plug (Type A)

Data transmission: max. 18 Gbit/s

Other formats: 4K Ultra HD, 4K 3D, HEC, HDR, ARC, Audio 1536 Hz, x.v. Colour (xvYCC), YCbCr 4:4:4, Deep Color (36 Bit), 21:9 Cinemascope

- Insulation resistance: 300 V @ 10 MOhms
- Conductor resistance: 5/10 Ohms

- Colour: black

- Conformity: RoHS compliant

### Änderungen

| Datum      | Name | gez.:  | Datum      | Name |
|------------|------|--------|------------|------|
| 19.09.2019 | ss   | gez.:  | 18.09.2017 | tf   |
|            |      | gepr.: | 18.09.2017 | tf   |
|            |      | Norm:  |            |      |

Änderungen vorbehalten / Subject to change

Bezeichnung

HDMI™ HiSpeed Kabel /wE

Zeichnungs-Nr.:



Blatt

von