

Technical Material Data Sheet

1. Chemical Product and Company Identification

Model No.: 64558

Description: PowerBank 4000mAh (Micro-USB Kabel)

Nominal Voltage: 3.7 V

Typical Capacity: 4000 mAh, 14.80 Wh

Battery Weight: 69.2 g

Figure:



Model No.: 64559

Description: PowerBank 8000mAh (Micro-USB Kabel)

Nominal Voltage: 3.7 V

Typical Capacity: 8000 mAh, 29.60 Wh

Battery Weight: 140.0 g

Figure:



Company Information: Wentronic GmbH
Brand: Goobay®
Pillmannstraße 12
38112 Braunschweig
Germany

Phone: +49 (0) 531 / 210 58 0
Fax: +49 (0) 531 / 210 58 23

Emergency Telephone: +49 (0) 700 / 24 112 112
Prepared by: TF
Creation Date: 2016-02-08

Supplier Code: **#2219**
Checked and approved by: TL
Version: 1.0

Technical Material Data Sheet

2. Composition / Information on Ingredient

64558: PowerBank 4000mAh (Micro-USB Kabel)

Chemical Name	CAS No.	Weight (%)
LiCoO ₂	12190-79-3	≤0.00
LiMn ₂ O ₄	12057-17-9	≤0.00
Li (NiCoMn) O ₂	N/A	≤46.62
Graphite ©	7782-42-5	≤22.28
Poly Vnylidene Fluoride (PVDF)	24937-79-9	≤0.70
Acetylene Black	1333-86-4	≤1.39
Electrolyte	623-53-0 21324-40-3	≤16.80
Separator (PE)	N/A	≤7.30
PCBA	N/A	≤0.00

64559: PowerBank 8000mAh (Micro-USB Kabel)

Chemical Name	CAS No.	Weight (%)
SBR (CF ₂ -CF ₂) _n	9003-55-8	0.3
Acetylene Black (C)	1333-86-4	0.4
PVDF (-[CH ₂ -CFG ₂]-) _n	24937-79-9	0.9
Cobalt lithium dioxide (CoO ₂ Li)	12190-79-3	38.4
Graphite (C)	7782-42-5	18.2
Lithium hexafluorophosphate (LiPF ₆)	21324-40-3	0.3
Electrolyte (proprietary)	21324-40-3 96-49-1 616-38-6	38.2
Other	N/A	3.3

This Polymer lithium ion cell is a mixture.

Labeling according to EC directives.

No symbol and risk phrase are required.

Note: CAS number is Chemical Abstract Service Registry Number.

N/A: Not applicable.

Technical Material Data Sheet

3. Hazards Identification

Preparation hazards and classification	Not dangerous with normal use. Do not dismantle, open or shred Rechargeable polymer lithium ion battery. Exposure to the ingredients contained within or their ingredients products could be harmful.
Apperance, Color, and Odor	Solid object with no odor, silver.
Primary Route(s) of Exposure	These chemicals are contained in a sealed stainless steel enclosure. Risk of exposure occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, exposure to the electrolyte solution contained within can occur by Inhalation, Ingestion, Eye contact and Skin contact
Potential Health Effects:	ACUTE (short term): see Section 8 for exposure controls In the event that this battery has been ruptured, the electrolyte solution contained within the battery would be corrosive and can cause burns. Inhalation: Inhalation of materials from a sealed battery is not an expected route of exposure. Vapors or mists from a ruptured battery may cause respiratory irritation. Ingestion: Swallowing of materials from a sealed battery is not an expected route of exposure. Swallowing the contents of an open battery can cause serious chemical burns of mouth, esophagus, and gastrointestinal tract. Skin: Contact between the battery and skin will not cause any harm. Skin contact with contents of an open battery can cause severe irritation or burns to the skin. Eye: Contact between the battery and the eye will not cause any harm. Eye contact with contents of an open battery can cause severe irritation or burns to the eye. CHRONIC (long term): see Section 11 for additional toxicological data.
Medical Conditions Aggravated by Exposure	Not applicable
Reported as carcinogen	Not applicable

4. First Aid Measures

Inhalation	If contents of an opened battery are inhaled, remove source of contamination or move victim to fresh air. Obtain medical advice.
Skin contact	If skin contact with contents of an open battery occurs, as quickly as possible remove contaminated clothing, shoes and leather goods. Immediately flush with lukewarm, gently flowing water for at least 30 minutes. If irritation or pain persists, seek medical

Technical Material Data Sheet

	attention. Completely decontaminate clothing, shoes and leather goods before reuse or discard.
Eye contact	If eye contact with contents of an open battery occurs, immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 30 minutes while holding the eyelids open. Neutral saline solution may be used as soon as it is available. If necessary, continue flushin during transport to emergency care facility. Take care not to rinse contaminated water into the unaffected eye or onto face. Quickly transport victim to an emergency care facility.
Ingestion	If ingestion of contents of an open battery occurs, never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Have victim rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink 60 to 240 ml (2-8 oz.) of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Have victim rinse mouth with water again. Quickly transport victim to an emergency care facility.

5. Fire Fighting Measures

Flammable Properties	In the event that this battery has been ruptured, the electrolyte solution contain within the battery would be flammable. Like any sealed container, battery cells may rupture when exposed to excessive heat; this could result in the release of flammable or corrosive materials.
Suitable extinguishing Media	Use extinguishing media suitable for the materials that are burning.
Unsuitable extinguishing Media	Not available
Explosion Data	Sensitivity to Mechanical Impact: This may result in rupture in extreme cases Sensitivity to Static Discharge: Not Applicable
Specific Hazards arising from the chemical	Fires involving Rechargeable polymer lithium ion battery can be controlled with water. When water is used, however, hydrogen gas may evolve. In a confined space, hydrogen gas can form an explosive mixture. In this situation, smothering agents are recommended to extinguish the fire
Protective Equipment and precautions for firefighters	As for any fire, evacuate the area and fight the fire from a safe distance. Wear a pressure-demand, self-contained breathing apparatus and full protective gear. Fight fire from a protected location or a safe distance. Use NIOSH/MSHA approved full-face self-contained breathing apparatus (SCBA) with full protective gear.
NFPA	Health: 0 Flammability: 0 Instability: 0

Technical Material Data Sheet

6. Accidental Release Measures

Personal Precautions, protective equipment, and emergency procedures	Restrict access to area until completion of clean-up. Do not touch the spilled material. Wear adequate personal protective equipment as indicated in Section 8.
Environmental Precautions	Prevent material from contaminating soil and from entering sewers or waterways.
Methods and materials for Containment	Stop the leak if safe to do so. Contain the spilled liquid with dry sand or earth. Clean up spills immediately.
Methods and materials for cleaning up	Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into an acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Section 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal.

7. Handling and Storage

Handling	<p>Don't handling Rechargeable polymer lithium ion battery with metalwork. Do not open, disassemble, crush or burn battery. Ensure good ventilation/ exhaustion at the workplace. Prevent formation of dust. Information about protection against explosions and fires: Keep ignition sources away- Do not smoke.</p>
Storage	<p>If the Rechargeable polymer lithium ion battery are subject to storage for such a long term as more than 6 months, it is recommended to recharge the Rechargeable polymer lithium ion battery periodically.</p> <p>Storage Temperature Short period less than 1 month: -20°C~+45°C Short period less than 6 months: -10°C~+35°C Humidity : 65±20 % RH</p> <p>Do not storage Rechargeable polymer lithium ion cell haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects. Keep out of reach of children. Do not expose Rechargeable polymer lithium ion cell to heat or fire. Avoid storage in direct sunlight. Do not store together with oxidizing and acidic materials. Do not store together with oxidizing and acidic materials. Keep container tightly sealed.</p>

8. Exposure Controls, Personal Protection

Engineering Controls	<p>Use local exhaust ventilation or other engineering controls to control sources of dust, mist, fumes and vapor. Keep away from heat and open flame. Store in a cool, dry place.</p>
----------------------	--

Technical Material Data Sheet

Personal Protective Equipment	Respiratory Protection: Not necessary under normal conditions. Skin and body Protection: Not necessary under normal conditions, Wear neoprene or nitrile rubber gloves if handling an open or leaking battery. Hand protection: Wear neoprene or natural rubber material gloves if handling an open or leaking battery. Eye Protection: Not necessary under normal conditions, wear safety glasses if handling an open or leaking battery.
Other Protective Equipment	Have a safety shower and eye wash fountain readily available in the immediate work area.
Hygiene Measures	Do not eat, drink, or smoke in work area. Maintain good housekeeping.

9. Physical and Chemical Properties

Physical State	Form: Solid
	Color: Silver
	Odour: Monotony
Change in condition:	
pH, with indication of the concentration	Not applicable.
Melting point/freezing point	Not available.
Boiling Point, initial boiling point and Boiling range:	Not available.
Flash Point	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapor Pressure:	Not applicable
Vapor Density: (Air = 1)	Not applicable
Density/relative density	Not available.
Solubility in Water:	Insoluble.
n-octanol/water partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Odour threshold	Not available.
Evaporation rate	Not available.
Flammability (soil, gas)	Not available.
Viscosity	Not applicable.

10. Stability and Reactivity

Stability	The product is stable under normal conditions.
Conditions to Avoid (e.g. static discharge, shock or vibration)	Do not subject Rechargeable polymer lithium ion battery to mechanical shock. Vibration encountered during transportation does not cause leakage, fire or explosion. Do not disassemble,

Technical Material Data Sheet

	crush, short or install with incorrect polarity. Avoid mechanical or electrical abuse.
Incompatible Materials	Not Available.
Hazardous Decomposition Products	This material may release toxic fumes if burned or exposed to fire.
Possibility of Hazardous Reaction	Not Available.

11. Toxicological Information

Irritation	Risk of irritation occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, irritation to the skin, eyes and respiratory tract may occur.
Sensitization	Not Available
Neurological Effects	Not Available
Teratogenicity	Not Available
Reproductive Toxicity	Not Available
Mutagenicity (Genetic Effects)	Not Available
Toxicologically Synergistic Materials	Not Available

12. Ecological Information

General note:	Water hazard class 1 (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Anticipated behavior of a chemical product in environment/possible environmental impact/ecotoxicity	Not Available
Mobility in soil	Not Available
Persistence and Degradability	Not Available
Bioaccumulation potential	Not Available
Other Adverse Effects	Not Available

13. Disposal Considerations

Product disposal recommendation: Observe local, state and federal laws and regulations.
 Packaging disposal recommendation: Be aware discarded batteries may cause fire, tape the battery terminals to insulate them. Don't disassembly the battery. Completely discharge containers(no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local, state and federal laws and regulations.

Technical Material Data Sheet

14. Transport Information

For the international transport of lithium batteries, they must comply with these regulations: The International Maritime Dangerous Goods (IMDG) Code by International Maritime Organization (IMO), Dangerous Goods Regulations (DGR) by International Air Transport Association (IATA) and Technical Instructions for the Safe Transport of Dangerous Goods by Air (TI) by International Civil Aviation Organization (ICAO). These regulations are based on the UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria.

Lithium batteries which meet the requirements of UN38.3 (UN Manual of Tests and Criteria, Part III, subsection 38.3) could be transported by air and by sea as ordinary goods, otherwise should be transported according to Class 9, Packing Group II hazardous goods.

1. For Rechargeable polymer lithium ion battery, **UN 3480**. For Rechargeable polymer lithium ion battery contained in equipment or Rechargeable polymer lithium ion battery packed with equipment, **UN 3481**.
2. The consignment should be fully described by proper shipping name and packed, marked and in proper condition for carriage by air. The consignment is not classified as dangerous under the current edition of the IATA 56th Effective, Dangerous goods regulation and all applicable carrier and government regulations.
3. For transported by air, Lithium-ion Cells/Batteries shipped as "Not Restricted" Cargo must comply with Section II/ Section IB of PI965 or Section II of P966-PI967 accordingly; For cells, the Watt-hour rating should not be more than 20Wh; For batteries, the Watt-hour rating should not be more than 100Wh. Watt- hour rating must be marked on the outside of the battery case (marked by manufacturer).
4. Each consignment must be accompanied with a document such as an air waybill with an indication. For those Lithium ion cells/ batteries contained in equipment, the equipment must be equipped with an effective means of preventing accidental activation.
5. Quantity per package shall not exceed 10 kg in Section IB of PI965. Quantity per package shall not exceed 5 kg in Section II of PI966-PI967.
6. For only lithium battery transparent or lithium battery packed with equipment transparent, Each package must be capable of withstanding a 1.2 m drop test in any orientation without damage of cells or batteries contained therein.
7. Rechargeable polymer lithium ion battery which meet the requirements of 606090P could be transported by air, and the batteries manufactured meet these requirements. 606090P Rechargeable polymer lithium ion battery identified by the manufacturer as being defective for safety reasons, or that have been damaged, that have the potential of producing a dangerous evolution of heat, fire or short circuit are forbidden for transport.
8. Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to short circuit.

15. Regulatory Information

Law Information

- Dangerous Goods Regulation
- Recommendations on the Transport of Dangerous Goods Model Regulations
- International Maritime Dangerous Goods
- Classification and Code of Dangerous Goods
- OSHA Hazard Communication Standard Status
- Toxic Substances Control Act (TSCA) Status

In accordance with all Federal, State and Local Laws.

Technical Material Data Sheet

The products are not subject to dangerous goods.

16. Additional Information

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. Although reasonable precautions have been taken in the preparation of the data contained herein, it is offered solely for your information, consideration and investigation. This material safety data sheet provides guidelines for the safe handling and use of this product; it does not and cannot advise on all possible situations, therefore, your specific use of this product should be evaluated to determine if additional precautions are required. The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.